

MetersUSA
Meters@MetersUSA.com
www.MetersUSA.com

Saxon Indicators

MetersUSA
Meters@MetersUSA.com
www.MetersUSA.com

A.C. Ammeter



Rating	Scaling	Catalogue No.
A.C. Ammeter True RMS Reading - Accuracy ±2% ES		
5A	0.5a	(01*)-75AA-lsls-C6-B*
10A	0.10a	(01*)-75AA-mtmt-C6-B*
15A	0.15a	(01*)-75AA-ndnd-C6-B*
20A	0.20a	(01*)-75AA-ngng-C6-B*
30A	0.30a	(01*)-75AA-nlnl-C6-B*
1A	Transformer Rated	(01*)-75AA-LA**-C6-B*
5A	Transformer Rated	(01*)-75AA-LS**-C6-B*

A.C. Voltmeter True RMS Reading - Accuracy ±2% ES

150v	0-150V	(01*)-75VA-PZPZ-C6-B*
300v	0-300V	(01*)-75VA-RXR-X-C6-B*
600v	0-600V	(01*)-75VA-SJSJ-C6-B*
150V	transformer Rated	(01*)-75VA-PZ**-C6-B*

D.C. Ammeters - Accuracy ±2% ES

0.1mA	To Suit Requirements	(01*)-01AA-FA**-B*
0.5mA	0.5mA	(01*)-01AA-FXFX-B*
0-10mA	0-10mA	(01*)-01AA-GZGZ-B*
0.20mA	0.20mA	(01*)-01AA-HFHF-B*
0.50mA	0.50mA	(01*)-01AA-HYHY-B*
0-100mA	0-100mA	(01*)-01AA-JRJR-B*
0.200mA	0.200mA	(01*)-01AA-KAKA-B*
0.500mA	0.500mA	(01*)-01AA-KMKM-B*
0.600mA	0.600mA	(01*)-01AA-KPKP-B*
0.1A	0.1A	(01*)-01AA-LALA-B*
0.2A	0.2A	(01*)-01AA-LELE-B*
0.4A	0.4A	(01*)-01AA-LLLL-B*
0.5A	0.5A	(01*)-01AA-LSLB-B*
0.6A	0.6A	(01*)-01AA-LWLW-B*
0.10A	0.10A	(01*)-01AA-TMTT-B*
0.50mV	To Suit	(01*)-01AA-EC**-B*
0-100mV	To Suit	(01*)-01AA-GB**-B*

Milliammeters Suppressed Zero - Accuracy ±2% ES

4-20mA	To Suit Requirements	(01*)-01RA-HG**-B* **Specify scale value
--------	----------------------	---

D.C. Voltmeters Sensitivity 1000Ω/Volt - Accuracy ±2% ES

0.15V	0.15V	(01*)-01VA-NDND-B*
0.30V	0.30V	(01*)-01VA-NLNL-B*
0.50V	0.50V	(01*)-01VA-NTNT-B*
0.150V	0.150V	(01*)-01VA-PZPZ-B*
0.300V	0.300V	(01*)-01VA-RXR-X-B*
0.600V	0.600V	(01*)-01VA-SJSJ-B*

Frequency Meters 120V - Self Contained

50Hz	45-55Hz	(01*)-41SA-PNAG-AG-B*
55Hz	45-65Hz	(01*)-41SA-PNAJ-AJ-B*
60Hz	55-65Hz	(01*)-41SA-PNAN-AN-B*

Elapsed Time Meters 99999.99 hours - non reset

110/130V, 50Hz	-	(01*)-155A-PNZH-C5-B*
200/250V, 50Hz	-	(01*)-155A-RNZH-C5-B*
480V, 50Hz	-	(01*)-155A-SEZH-C5-B*
110/130V, 60Hz	-	(01*)-156A-PNZH-C6-B*
200/250V, 60Hz	-	(01*)-156A-RNZH-C6-B*
480V, 60Hz	-	(01*)-156A-SEZH-C6-B*

For an alternate voltage rating of 200-250V use code RN instead of PN

For an alternate voltage rating of 380-480V use code SE instead of PN

To denote the required case size, replace the 01* in the catalogue number with 012, 013 or 014 for 2 1/2", 3 1/2" or 4 1/2" respectively.

To denote the required stud fixing configuration, replace B* with B2 (2 stud), B3 (3 stud) or B4 (4 stud)

